

# PUR-WALL B | SAFETY DATA SHEET (SDS)

### **SECTION 1 - IDENTIFICATION**

Product identifier	PUR-WALL B
Other means of identification	None
Recommended use and restrictions on use	Construction product / Refer to technical information
Initial supplier identifier	PUREPOXY 301, rue Omer-DeSerres #105, Blainville, Quebec, CANADA J7C 0K2 Phone – 438-492-4450
Emergency telephone number/restriction on use	Canada – CANUTEC 24 hour number <b>613-996-6666</b>

#### **SECTION 2 - HAZARD IDENTIFICATION**

<b>Classification of hazardous product</b> (name of the category or subcategory of the hazard class)	Acute Toxicity, Oral (Category 4) Acute Toxicity, Dermal (Category 5) Skin Sensitization (Category 1A) Skin Corrosion/irritation (Category 1B) Serious eye damage/irritation (Category 1) Reproductive toxicity (Category 2) Hazardous to the aquatic environment - acute (Category 1) Hazardous to the aquatic environment - chronic (Category 1)
Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)	<ul> <li>H302 Harmful if swallowed</li> <li>H315 Causes skin irritation</li> <li>H317 May cause an allergic skin reaction</li> <li>H314 Causes severe skin burns and eye damage</li> <li>H361 Suspected of damaging fertility or the unborn child</li> <li>H400 Very toxic to aquatic life</li> <li>H410 Very toxic to aquatic life with long lasting effects</li> </ul>

P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust or mist. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P272 Contaminated work clothing should not be allowed out of the workplace. P270 Do not eat, drink or smoke when using this product. P264 Wash with plenty of water and soap thoroughly after handling. P308 + P313 IF exposed or concerned: Get medical advice/attention. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [shower]. P310 Immediately call a POISON CENTER or doctor/physician. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor/...if you feel unwell. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P362 + P364 Take off contaminated clothing and wash before reuse. P391 Collect spillage. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

**Other Hazards Known** 

None

## **SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name (common name/synonyms)	CAS NUMBER or other	Concentration (%)
Epoxy adduct	Trade secret	10 - 30
Isophorone diamine	2855-13-2	10 - 30
Benzyl alcohol	100-51-6	1 - 10
4-nonylphenol, branched	84852-15-3	10 - 30
Polyoxypropylene diamine	9046-10-0	20 - 40

All ingredients are listed according to OSHA (29 CFR).

\* Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) considered trade secret(s).

#### **SECTION 4 - FIRST AID MEASURES**

Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a doctor.	
Ingestion	IF SWALLOWED: Rinse mo	uth. Do NOT induce vomiting. Call a doctor if you feel unwell.
Skin contact	IF ON SKIN: wash with pler	nty of water (15-20 minutes). IF SKIN irritation or rash occurs: Get medical attention.
Eye contact	IF IN EYES, Rinse cautiously to do. Continue rinsing.	y with water for several minutes (15-20). Remove contact lenses, if present and easy
Most importan (acute and delaye	<b>t symptoms and effects</b> ed)	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of in attention/spec	nmediate medical ial treatment	In all cases, call a doctor. Do not forget this document.

#### **SECTION 5 - FIREFIGHTING MEASURES**

Specific hazards of the hazardous product (hazardous combustion products)	Carbon oxides and other irritant/toxic gases and fumes.
Suitable and unsuitable extinguishing media	In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish.
Special protective equipment and precautions for fire-fighters	During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

#### **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	Absorb spillage to prevent material-damage. Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).
Methods and materials for containment and cleaning up	Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

## **SECTION 7 - HANDLING AND STORAGE**

Precautions for	Wear protective gloves/ protective clothing/ eye protection/ face protection.	
safe handling	Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/ spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.	
Conditions for safe storage, including any incompatibilities	Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.	

## **SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**

<b>Control Parameters</b> (biological limit values or exposure limit values and source of those values)	Exposure limits: None known
Appropriate engineering controls	Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.
Individual protection measures/personal protective equipment	Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.

#### **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Appearance / color	Paste, Opaque color	Vapour pressure	Not available
Odour	Characteristic	Vapour density	Not available
Odour threshold	Not available	Relative density	1.0223 g/ml
рН	Not available	Solubility	Partial
Melting point / Freezing point	Not available	Partition coefficient of n-octanol/water	Not available
Initial boiling point/ranges	Not available	Auto-ignition temperature	Not available
Flash point	> 199°F (93°C)	<b>Decomposition temperature</b>	Not available
Evaporation rate	Not available	Viscosity	275,000-300,000 cps
Flammability (solid, gas)	Not available	VOC	200.5 g/L
Upper/Lower flammability or explosive limits	Not available	Other	None know

## **SECTION 10 - STABILITY AND REACTIVITY**

Reactivity	Does not react under the recommended storage and handling conditions prescribed.
Chemical Stability	This product is stable under normal conditions
Possibility of hazardous reactions	This product will polymerize if mixed with an amine. Considerable heat can evolve.
<b>Conditions to avoid</b> (static discharge, shock or vibration)	Avoid temperatures exceeding the flash point. Avoid unintended contact with amines.
Incompatible materials	Oxidizing materials; etc.
Hazardous decomposition products	None known

## **SECTION 11 - TOXICOLOGICAL INFORMATION**

<b>Information on the likely routes</b> <b>of exposure</b> (inhalation, ingestion, skin and eye contact)	May be harmful if inhaled. Harmful if swallowed. May be harmful in contact with skin. May cause an allergic skin reaction. Causes severe skin burns. Causes serious eye damage.
Symptoms related to the physical, chemical and toxicological characteristics	Contains ingredients which are extremely destructive to tissues of the mucous membranes and upper respiratory tract, eyes, and skin. Burning pain and severe corrosive skin damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing, shortness of breath, headaches, and nausea
<b>Delayed and immediate effects</b> (chronic effects from short-term and long-term exposure)	Skin Sensitization – possible; Respiratory Sensitization – No data available; Germ Cell Muta- genicity – No data available; Carcinogenicity – No ingredient listed by IARC, ACGIH, NTP or OSHA; Reproductive Toxicity – Suspected of damaging fertility or the unborn child; Specific Target Organ Toxicity — Single Exposure – No data available; Specific Target Organ Toxici- ty — Repeated Exposure – No data available; Aspiration Hazard – No data available; Health Hazards Not Otherwise Classified – No data available.
Numerical measures of toxicity (ATE; LD <sub>50</sub> & LC <sub>50</sub> )	CAS Proprietary No data available CAS 2855-13-2 $LD_{50}$ , Oral - Rat 1030 mg/kg CAS 100-51-6 $LD_{50}$ , Oral - Rat 1360 mg/kg CAS 84852-15-3 $LD_{50}$ , Oral- Rat - 1300 mg/kg; $LD_{50}$ , Dermal- Rabbit - 3160 mg/kg CAS 9046-10-0 $LD_{50}$ , Oral- Rat - 2885.3 mg/kg $LD_{50}$ , Inhalation - Rat - 8h > 0.74 mg/l ATE not available in this document.

## **SECTION 12 - ECOLOGICAL INFORMATION**

Very toxic to aquatic life with long lasting effects
No data available
Bioconcentration potential is moderate.
Low potential for mobility in soil.
No data available

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

#### Information on safe handling for disposal/methods of disposal/contaminated packaging

Do not discharge substance/product into sewer system. Avoid release to the environment. Dispose of contents/container into safe container in accordance with local, regional or national regulations.

### **SECTION 14 - TRANSPORT INFORMATION**

UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations: UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime): UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air): UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III

Special Precautions (transport/conveyance): None Environmental hazards (IMDG or other): Marine Pollutant Bulk transport (usually more than 450L in capacity): Possible

#### **SECTION 15 - REGULATORY INFORMATION**

Safety/health Canadian regulations specifics	Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).	
Environmental Canadian regulations specifics	Refer to Section 3 for ingredient(s) of the DSL	
Safety/health/environmental outside regulations specifics Bioaccumulative potential	United States OSHA information: This product is regulated according to OSHA (29 CFR). United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14.	
	United States TCSA information: Refer to the ingredients listed in Section 3.	
National Fire Protection Association (NFPA)	HEALTH: 3 FLAMMABILITY: 2 INSTABILITY: 0 SPECIAL HAZARDS: Refer to Section 2 & 3. HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe	

#### **SECTION 16 - OTHER INFORMATION**

Date of the latest revision of the safety data sheet	Febuary 24, 2020 version 5		
Corrections	SDS Template modifications		
References	Safety Data Sheets from manufacturer/supplier		
Abbreviations	ACGIH ATE CAS DSL IARC IATA IMDG LC LD NIOSH NTP OSHA PEL STEL TDG TLV TSCA TWA WHMIS	American Conference of Governmental Industrial Hygienists Acute toxicity estimate Chemical Abstract Service Domestic Substance List International Agency for Research on Cancer International Air Transport Association International Maritime Dangerous Goods Code Lethal concentration Lethal Dosage National Institute for Occupational Safety and Health National Toxicology Program (U.S.A.) Occupational Safety and Health Administration (U.S.A.) Permissible Exposure Limit Short-term Exposure Limit Transport of dangerous goods in Canada Threshold Limit Value Toxic Substances Control Act Time Weighted Average Workplace Hazardous Materials Information System	

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.