

FLEXDECK PRIMER

Two-Component, High Solids, Epoxy-Polyamine Filler Surfacer Primer



REVISION : 04/22/2022

PART A | SAFETY DATA SHEET (SDS)

SECTION 1 - IDENTIFICATION

| | |
|--|--|
| Product identifier | FLEXDECK PRIMER, PART-A |
| Other means of identification | None |
| Recommended use and restrictions on use | Construction product / Refer to technical information |
| Initial supplier identifier | PUREPOXY 4400 A. Chomedey W. Laval, QC CANADA H7R 6E9 Tel: (450) 818-0626 |
| Emergency telephone number/restriction on use | Canada – CANUTEC 24 hour number 613-996-6666 |

SECTION 2 - HAZARD IDENTIFICATION

| | |
|---|--|
| Classification of hazardous product (name of the category or subcategory of the hazard class) | Specific Target Organ Toxicity - Repeated Exposure - Category 2 Skin Irritation - Category 2 Skin Sensitizer - Category 1 Carcinogenicity - Category 2 Eye Irritation - Category 2 Chronic aquatic toxicity - Category 2 Acute aquatic toxicity - Category 2 |
|---|--|

Information elements
(symbols, signal words, hazard statements and precautionary statements of the category/subcategory)



WARNING

H373 - May cause damage to organs through prolonged or repeated exposure.
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H351 - Suspected of causing cancer.
H319 - Causes serious eye irritation
H401 - Toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects

P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read label before use. P260 - Do not breathe dust/fume/gas/mist/vapors/spray. P264 - Wash thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P272 - Contaminated work clothing should not be allowed out of the workplace. P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P273 - Avoid release to the environment. P314 - Get Medical advice/attention if you feel unwell. P302 + P352 - IF ON SKIN: Wash with plenty of water. P321 - Specific treatment (see section 4 on this SDS). P332 + P313 - If skin irritation occurs: Get medical advice/attention. P362 + P364 - Take off contaminated clothing. And wash it before reuse. P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention. P308 + P313 - IF exposed or concerned: Get medical advice/attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice/attention. P391 - Collect spillage. P405 - Store locked up. P501 - Dispose of contents/ container to an approved waste disposal plant.

| | |
|----------------------------|------|
| Other Hazards Known | None |
|----------------------------|------|

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name (common name/synonyms) | CAS NUMBER or other | Concentration (%) |
|--|---------------------|-------------------|
| BISPHENOL A EPOXY RESIN | 25068-38-6 | 35 - 65 |
| KAOLIN | 1332-58-7 | 13 - 25 |
| SILICA, CRYSTALLINE | 14808-60-7 | 11 - 20 |
| OXIRANE, 2-[[2-ETHYLHEXYL)OXY]METHYL]- | 2461-15-6 | 9 - 17 |
| DI(2-ETHYLHEXYL)ADIPATE | 103-23-1 | < 3 |
| CARBON BLACK | 1333-86-4 | < 1 |

All ingredients are listed according to OSHA (29 CFR).

* Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) considered trade secret(s).

SECTION 4 - FIRST AID MEASURES

| | |
|--|---|
| Inhalation | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a doctor. |
| Ingestion | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a doctor if you feel unwell. |
| Skin contact | IF ON SKIN: wash with plenty of water (15-20 minutes). IF SKIN irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. |
| Eye contact | IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue rinsing. |
| Most important symptoms and effects (acute and delayed) | No data available. |
| Indication of immediate medical attention/special treatment | No data available. |

SECTION 5 - FIREFIGHTING MEASURES

| | |
|--|--|
| Specific hazards of the hazardous product (hazardous combustion products) | Excessive pressure or temperature may cause explosive rupture of containers. |
| Suitable and unsuitable extinguishing media | Dry chemical, foam, carbon dioxide water spray or fog is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only. |
| Fire-fighting Procedures | Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. |
| Special protective equipment and precautions for fire-fighters | Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear. Care should always be exercised in dust/mist areas. |

SECTION 6 - ACCIDENTAL RELEASE MEASURES

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Absorb spillage to prevent material-damage. Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8). |
| Methods and materials for containment and cleaning up | Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required. |

SECTION 7 - HANDLING AND STORAGE

| | |
|---|---|
| Precautions for safe handling | Wear protective gloves/ protective clothing/ eye protection/ face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8. |
| Conditions for safe storage, including any incompatibilities | Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials. Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks. |

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

| | |
|---|---|
| Control Parameters (biological limit values or exposure limit values and source of those values) | Exposure limits: None known |
| Appropriate engineering controls | Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. |
| Individual protection measures/personal protective equipment | Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use. |

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|---|-------------------|---|------------------|
| Appearance / color | Pigmented Liquid | Vapour Density | Heavier than air |
| Odour | Characteristic | Specific Gravity | 1.33 |
| Odour threshold | Not available | Density | 11.13 lb/gal |
| pH | Not available | Solubility | Not available |
| Melting point / Freezing point | Not available | Partition coefficient of n-octanol/water | Not available |
| Low boiling point | 464°F (240°C) | Auto-ignition temperature | Not available |
| Flash point | > 199.4°F (93°C) | Decomposition temperature | Not available |
| Evaporation rate | Slower than ether | Viscosity | 1200 - 1400 cps |
| Flammability (solid, gas) | Not available | VOC | Not available |
| Upper/Lower flammability or explosive limits | Not available | Other | None know |

SECTION 10 - STABILITY AND REACTIVITY

| | |
|--|--|
| Reactivity | Does not react under the recommended storage and handling conditions prescribed. |
| Chemical Stability | Stable under the recommended storage and handling conditions prescribed. |
| Possibility of hazardous reactions | Will not occur but aliphatic amine will cause irreversible polymerization with considerable heat build up. |
| Conditions to avoid (static discharge, shock or vibration) | Heat, high temperature, open flame, sparks, and moisture. Contact with incompatible materials in a closed system will cause buildup of pressure. |
| Incompatible materials | Oxidizing materials; etc. |
| Hazardous decomposition products | Combustion products: organic vapors and thermal decomposition fragments. |

SECTION 11 - TOXICOLOGICAL INFORMATION

| | |
|---|---|
| Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact) | Repeated skin contact may cause a persistent irritation or dermatitis. May also aggravate an existing skin condition. Causes skin irritation. Causes serious eye irritation. Exposure may cause mucous membrane and respiratory tract irritation, tightness of chest, headache, shortness of breath, and a dry cough. The effects of acute exposure may be delayed in onset up to 12-24 hours. Repeated exposure above current occupational limits may cause an allergic sensitization of the respiratory tract. This is characterized by an asthma-like response upon re-exposure to the chemical. The symptoms may include coughing, wheezing, shortness of breath and chest tightness. May cause an allergic skin reaction |
| Symptoms related to the physical, chemical and toxicological characteristics | Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing; |
| Delayed and immediate effects (chronic effects from short-term and long-term exposure) | Skin Sensitization – Possible; Respiratory Sensitization – Possible; Germ Cell Mutagenicity – No data available; Carcinogenicity – Suspected of causing cancer; Reproductive Toxicity – No data available; Specific Target Organ Toxicity – Single Exposure – No data available; Specific Target Organ Toxicity – Repeated Exposure – May cause damage to organs through prolonged or repeated exposure; Aspiration Hazard – No data available; Health Hazards Not Otherwise Classified – No data available. |
| Numerical measures of toxicity (ATE; LD ₅₀ & LC ₅₀) | 0001333-86-4 LC ₅₀ (rat): 6750 mg/m ³ (4-hour exposure); cited as 27000 mg/m ³ (27 mg/L) (1-hour exposure) (3); ATE not available in this document. |

SECTION 12 - ECOLOGICAL INFORMATION

| | |
|--|--|
| Ecotoxicity (aquatic and terrestrial information) | Toxic to aquatic life. Toxic to aquatic life with long lasting effects |
| Persistence and degradability | No data available |
| Bioaccumulative potential | Bioconcentration potential is moderate |
| Mobility in soil | No data available. |
| Other adverse effects | No data available |

SECTION 13 - DISPOSAL CONSIDERATIONS

Information on safe handling for disposal/methods of disposal/contaminated packaging

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

SECTION 14 - TRANSPORT INFORMATION

UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations: NOT REGULATED

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime):

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III

Special Precautions (transport/conveyance): May also be shipped as a LIMITED QUANTITY in accordance with TDG.

Environmental hazards (IMDG or other): Marine Pollutant

Bulk transport (usually more than 450L in capacity): Possible

SECTION 15 - REGULATORY INFORMATION

| | |
|--|--|
| Safety/health Canadian regulations specifics | Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR). |
| Environmental Canadian regulations specifics | Refer to Section 3 for ingredient(s) of the DSL |
| Safety/health/environmental outside regulations specifics Bioaccumulative potential | United States OSHA information: This product is regulated according to OSHA (29 CFR). United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14. United States TCSA information: Refer to the ingredients listed in Section 3. |
| National Fire Protection Association (NFPA) | HEALTH: 2 FLAMMABILITY: 1 INSTABILITY: 1 SPECIAL HAZARDS: Refer to Section 2 & 3. HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe |

SECTION 16 - OTHER INFORMATION

| | |
|---|--|
| Date of the latest revision of the safety data sheet | April 22, 2020 version 5 |
| Corrections | SDS Template modifications |
| References | Safety Data Sheets from manufacturer/supplier |
| Abbreviations | ACGIH American Conference of Governmental Industrial Hygienists ATE Acute toxicity estimate CAS Chemical Abstract Service DSL Domestic Substance List IARC International Agency for Research on Cancer IATA International Air Transport Association IMDG International Maritime Dangerous Goods Code LC Lethal concentration LD Lethal Dosage NIOSH National Institute for Occupational Safety and Health NTP National Toxicology Program (U.S.A.) OSHA Occupational Safety and Health Administration (U.S.A.) PEL Permissible Exposure Limit STEL Short-term Exposure Limit TDG Transport of dangerous goods in Canada TLV Threshold Limit Value TSCA Toxic Substances Control Act TWA Time Weighted Average WHMIS Workplace Hazardous Materials Information System |

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.